

DATACARD® SD260 CARD PRINTER



새로운 모습의 리더십

SD260 카드 프린터는 뛰어난 인쇄 품질과 신뢰성, 작동의 용이성 및 공간 효율성을 높인 새로운 모습의 리더십을 제공합니다.

모두를 위한 최고 가치의 카드 발급 프린터

Datacard® SD260 카드프린터의 사용을 위한 교육에 시간과 비용을 투자하지 마십시오. 업계를 선도하는 혁신기술을 접목하여 ID카드 인쇄를 쉽고, 경제적으로 할 수 있습니다. SD260은 바쁜 업무중에 ID 카드를 인쇄하는 모든 이들에게 이상적입니다. 경쟁력 있는 기능과 가격을 갖춘 SD260은 최고의 가치를 선사합니다. 하지만 진정한 가치는 저희가 고객을 위하여 모든 것을 고려했다 최고의 혁신 기술들이 적용된 최고의 카드 프린터

- **누구나 사용할 수 있는 쉬운 작동방법.** 소프트 터치 패널과 LCD 화면상의 아이콘을 통해 쉽게 사용하실 수 있습니다. 카드 및 소모품 장착이 용이하고, 클리닝 롤러를 포함한 리본 카트리지는 사용자의 편의성에 중점을 두어 설계되었습니다.
- **우수한 이미지 품질.** 새로운 TrueMatch™ 인쇄 기술은 선명한 색상과 역동적이면서도 깨끗한 인쇄 품질을 보장합니다. 고성능 프린터 드라이버는 최신 Microsoft® XPS 기반 기술을 사용하여 속도와 이미지 품질을 극적으로 향상시켰습니다. 처음부터 마지막 카드 인쇄 작업까지, 일관되게 좋은 결과물을 얻을 수 있습니다.
- **신뢰할 수 있는 성능과 우수한 속도.** 업계 내에서의 독보적인 TruePick™ 기술은 카드의 두께에 따라 매번 프린터 설정을 변경하지 않아도 정확하게 카드를 투입시켜 줍니다. 또한 새롭게 선보인 정교한 프린트헤드 기술은 생산속도를 전반적으로 높여줍니다.
- **연결을 위한 간편한 설정.** Ethernet 및 USB 포트, 브라우저 기반의 프린터 관리자 기능을 활용해 거의 모든 애플리케이션 및 IT환경에 SD260 프린터를 연결하여 사용할 수 있습니다.

DATACARD® SD260 CARD PRINTER

Color and monochrome print capabilities in the same printer

Manual feed or automatic 100-card input hopper


Intuitive LCD panel with soft touch controls

25-card output hopper standard with optional 100-card output hopper



All-in-one supply cartridges with drop-in cleaning roller

Advanced printer driver – support for third-party application development



Ethernet and USB connectivity

SD260 Standard Features

Print capabilities

- One-sided, edge-to-edge printing; manual duplex printing
- Full-color and monochrome printing capability
- Alphanumeric text, logos and digitized signatures
- Variety of bar codes: 1D/2D bar code images

Print resolution

- 300 dots per inch, 256 shades per color panel

Print quality

- Ability to conform to Microsoft® sRGB standard
- End-to-end color management

Print speed

- Full-color printing: up to 190 cards per hour
- Monochrome printing: up to 800 cards per hour

Printer display

- Printer status messages
- Multiple backlight settings

Card capacity

- Automatic feed: 100-card input for 0.030 in. (0.76mm) cards, 25-card output standard
- Manual feed: One card input; 5-card output for 0.030 in. (0.76mm) cards

Printer driver

- Adjustable color controls with image preview
- Pre-set area to block printing on magnetic stripe, with escapes for custom areas
- Utilizes Windows® XPS-based technology for high-fidelity printing
- Secure disabling of card remake

User-friendly operation

- Printer messages display on LCD panel
- Graphical display on Windows 7 and Windows Vista® operating systems
- Easy, fast installation
- Card remake standard with cancel option
- Operator-replaceable printhead
- Front panel soft power button

Datacard® Certified Supplies featuring Intelligent Supplies Technology™

- Automatic identification and validation for ribbons
- Adjustable low ribbon and cleaning card alerts
- Ribbon saver
- End-of-ribbon notices for full color ribbons

Warranties

- 30-month standard depot warranty
- 30-month printhead warranty (no pass restrictions)

SD260 Options

Magnetic Stripe Encoding

- ISO 7811 Three-track option
- JIS Type II Single-track option
- High- and low-coercivity
- Support for standard and custom data formats

Extended 100-card output hopper

Kensington® security lock for printer

SD260 Specifications

Physical dimensions

- L 15.4 in. x W 6.7 in. x H 8.7 in.
(39.0 cm x 17.0 cm x 22.1 cm)

Weight

- 10.0 lbs (4.6 kg) (depending on options)

Electronic requirements

- 100/120V, 50/60 Hz
- 220/240V, 50/60 Hz

Plastic cards accepted

- ISO ID-1/CR-80 size cards
- 3.370 in. x 2.125 in. (85.6 mm x 53.98 mm)
- PVC with glossy laminate surface
- Select key fob cards (ISO ID-1/CR-80 size cards)
- Datacard® StickiCard™ adhesive-backed plastic cards

Card thickness accepted

- 0.010 in. to 0.037 in. (0.254 mm to 0.939 mm)

Operating environment

- 60°F to 95°F (15°C to 35°C)
- 20% to 80% non-condensing humidity

Storage environment

- 5°F to 140°F (-15°C to 60°C)
- 10% to 90%, non-condensing humidity

Connectivity

- Bidirectional USB 2.0
- Ethernet 10 Base-T/100-Base-TX (with activity light)

Operating system support for printer driver

- Windows 7 (32 and 64 bit)
- Windows Vista® (32 and 64 bit)
- Windows 2008 Server (32 and 64 bit)
- Windows XP SP3 (32 bit)
- Windows 2003 Server R2 (32 bit)
- Microsoft Windows Hardware Quality Labs (WHQL) certified

Agency approvals

- cULus, FCC, I.C., CE, Ctick, VCCI, RoHS, WEEE, ENERGY STAR, CCC, KCC

Environment/energy-saving features

- ENERGY STAR qualified printer
- Biodegradable supply core
- Recyclable enclosure plastics (marked with recycle symbol per Resin Identification Code)
- Recyclable packaging

Included with SD260 printer:

- Printer Driver CD, Quick Install Guide and Warranty
- Cleaning Pen
- Cleaning Roller Spindle
- USB Cable
- Power Supply
- Power Cord (Region-specific)

Datacard Group

Corporate Headquarters

11111 Bren Road West
Minnetonka, Minnesota 55343-9015

Phone: +1 952 933 1223

www.datacard.com

info@datacard.com



Datacard, StickiCard, TrueMatch, Intelligent Supplies Technology and TruePick are trademarks, registered trademarks and/or service marks of DataCard Corporation in the United States and/or other countries. Microsoft, Windows and Windows Vista are registered trademarks of Microsoft Corporation. Kensington is a registered trademark of ACCO Brands Corporation. ENERGY STAR is a registered trademark owned by the U.S. Environmental Protection Agency. EcoPure is a trademark owned by Bio-Tec Environmental LLC. Names and logos on cards are fictitious. Any similarity to actual names, trademarks or tradenames is coincidental.

©2010 DataCard Corporation. All rights reserved. Specifications subject to change without notice.

DP10-9007